

HK REFRIGERATION

42, Rue Roger SALENGRO BP 205

69 741 GENAS - FRANCE

Tel. : +33(0)472 471 444 - Fax : +33(0)472 471 399

Email : customer.serv@lennoxemea.com

Item : **Item 16**Typ : **Cubic**

Date 05.01.2020

Version : 4.00

3C-A 3444 L (Multi Refrigerant)**Total capacity : 8,5 kW****DT1 (Dew) / DTM (Mean) : 6 / 8 K**

DeltaT1 = Difference between air inlet temperature and Dew temperature (Evaporator outlet before superheat).

Operating conditions

Refrigerant :	R449A
Room temperature :	0 °C
Unit number :	1
Pressure :	-1 bar / 25 bar

Aeraulic characteristics (per unit)

Nb. and diameter of fans :	4 x 300 mm
Air flow-rate :	5880 m3/h
Pressure :	0 Pa
Air throw :	23 m
Lp (at 4m) :	40 dB(A)

Coil characteristics (per unit)

Surface :	22.7 m2
Volume :	5,2 dm3
Fin spacing :	6 mm
Inlet / Outlet :	5/8"-7/8" (D)

Electrical characteristics (per unit)

Rotation speed :	1350 tr/min
Maximum input power :	4 x 73 W
Maximum operating current :	4 x 0,32 A
Motor coupling :	-
Voltage/ Nb Phases / Frequency :	230V / 1 / 50Hz

Dimensional characteristics (per unit)

Dimensions (L/D/H) :	1933/484/428 mm
Empty net weight :	52 kg
Packaging (L/D/H) :	2080 / 650 / 600 mm
Packed unit weight :	81 kg
Standard packaging :	Pallet

(1) The average acoustic pressure level in dB(A) measured at 4 m, at fan height, in direct line of sight on a reflective surface, are given as an example. Only the acoustic pressure spectrum and Lw value, are contractually binding and may be used to evaluate the pressure characteristics at the property boundaries.

HK REFRIGERATION

42, Rue Roger SALENGRO BP 205

69 741 GENAS - FRANCE

Tel. : +33(0)472 471 444 - Fax : +33(0)472 471 399

Email : customer.serv@lennoxemea.com



Item : **Item 16**

Typ : **Cubic**

Date 05.01.2020

Version : 4.00

Options 3C-A 3444 L

- ☒ E1U : Light electric defrost
- ☐ E1K : Light electric defrost
- ☐ E2K : Intermediate electric defrost + intermediate drain pan.
- ☐ E3K : Full electric defrost + intermediate drain pan.
- ☐ BXT : Blygold Polual XT coil protection.
- ☐ BAE : Paint coil protection.
- ☐ THD : Defrost thermostat (5709L).
- ☐ THS : Safety thermostat (5708L).
- ☐ 2TH : Defrost and safety thermostats (5709L + 5708L).
- ☐ HG1 : Hot gas (coil: hot gas, drain pan : electrical heaters)
- ☐ EIS : Insulated drain pan.
- ☐ RVU : Shell defrost heaters.
- ☐ RVK : Shell defrost heaters.
- ☐ DPK : Intermediate drain pan Kit (3C-A .. R/L).
- ☐ DMP : Expansion valve fitted Plus (With liquid line)
- ☐ EEC : EVL + copper siphon equipped with a ball valve
- ☐ PEI : White painted casing.
- ☐ EVL : DMP + solenoid valve fitted.
- ☐ BHE : Heresite coil protection.
- ☐ CIN : 316L Stainless steel frame.
- ☐ DEG : Hot glycol water defrost.
- ☐ PGI : Stainless steel end place

HK REFRIGERATION

42, Rue Roger SALENGRO BP 205

69 741 GENAS - FRANCE

Tel. : +33(0)472 471 444 - Fax : +33(0)472 471 399

Email : customer.serv@lennoxemea.com



Item : **Item 16**

Typ : **Cubic**

Date 05.01.2020

Version : 4.00

Model : 3C-A 3444 L

(Drawings are only indicative)

